

BUREAU INTERNATIONAL DES POIDS ET MESURES

International Reference System for activity measurements of gamma-ray emitting nuclides (SIR) (gas)

Participating laboratory: _____

Radionuclide (main contribution)

$T_{1/2}$: _____

Chemical composition of the gas:

Amount of radioactive gas: _____ mol. Amount of inactive gas (if any): _____ mol

Gas pressure at 20 °C in the ampoule: _____ Pa. Pressure value was measured ___ or calculated ___.

Volume of gas transferred in the ampoule at 20 °C: _____ cm³

Ampoule number: _____

Activity of the gas (main radionuclide): _____ Bq

Reference date: _____ year _____ month _____ day _____ h UTC*

Measurement date: _____

Uncertainties (in the form of standard uncertainties). **Please attach also a detailed uncertainty budget:**

Category A (evaluated applying statistical methods) : _____ Bq ; _____ %

Number of degrees of freedom: _____

Category B (evaluated by other means): _____ Bq ; _____ %

Method(s) of measurement: _____

For relative methods, please indicate the methods and the standards used to calibrate your experimental setup: _

and also the date of calibration: _____.

	Nuclide	Ratio of activity of impurity to activity of main radionuclide at reference date
Radionuclide impurities:	_____	(_____) %; $u =$ (_____) %
	_____	(_____) %; $u =$ (_____) %

Remarks: _____

This sample has been sent in the frame of a pilot study __ or to generate an equivalence value __.

Date: _____ Name of person responsible: _____

Name of person(s) who carried out
the measurements: _____

*UTC = coordinated universal time

January 18, 2011 Reference BIPM/RI-SIR-F-06(1.6)

Detailed Uncertainty Budget

Laboratory: _____; Radionuclide: _____ ; Ampoule number: _____ .

*Uncertainty components**, in % of the activity concentration, due to

	Remarks	Evaluation type (A or B)	Relative Sensitivity Factor
counting statistics	-----	-----	-----
weighing	-----	-----	-----
dead time	-----	-----	-----
background	-----	-----	-----
pile-up	-----	-----	-----
counting time	-----	-----	-----
adsorption	-----	-----	-----
impurities	-----	-----	-----
tracer	-----	-----	-----
input parameters and statistical model	-----	-----	-----
quenching	-----	-----	-----
interpolation from calibration curve	-----	-----	-----
decay-scheme parameters	-----	-----	-----
half life ($T_{1/2} =$ _____ ; $u =$ _____)	-----	-----	-----
self absorption	-----	-----	-----
extrapolation of efficiency curve	-----	-----	-----
other effects (if relevant) (explain)	-----	-----	-----
combined uncertainty (as quadratic sum of all uncertainty components)	-----	-----	-----

* The uncertainty components are to be considered as approximations of the corresponding standard deviations (see also *Metrologia*, 1981, 17, 73 and *Guide to expression of uncertainty in measurement*, ISO, corrected and reprinted 1995).

List of acronyms proposed to be used to identify different measurement methods

Each acronym has six components, geometry-detector (1)-radiation (1)-detector (2)-radiation (2)-mode. When a component is unknown, ?? is used and when it is not applicable 00 is used.

Geometry	acronym	Detector	acronym
4π	4P	proportional counter	PC
defined solid angle	SA	press. prop. counter	PP
2π	2P	liquid scintillation counting	LS
undefined solid angle	UA	Nal(Tl)	NA
		Ge(HP)	GH
		Ge(Li)	GL
		Si(Li)	SL
		Cs(Tl)	CS
		ionization chamber	IC
		grid ionization chamber	GC
		bolometer	BO
		calorimeter	CA
		PIPS detector	PS
Radiation	acronym	Mode	acronym
positron	PO	efficiency tracing	ET
beta particle	BP	internal gas counting	IG
Auger electron	AE	CIEMAT/NIST	CN
conversion electron	CE	sum counting	SC
mixed electrons	ME	coincidence	CO
bremsstrahlung	BS	anti-coincidence	AC
gamma rays	GR	coincidence counting with efficiency tracing	CT
X - rays	XR	anti-coincidence counting with efficiency tracing	AT
photons ($x + \gamma$)	PH	triple-to-double coincidence ratio counting	TD
photons + electrons	PE	selective sampling	SS
alpha - particle	AP	high efficiency	HE
mixture of various radiations	MX	digital coincidence counting	DC

Examples	
method	acronym
4π (PC) β - γ -coincidence counting	4P-PC-BP-NA-GR-CO
4π (PPC) β - γ -coincidence counting eff. trac.	4P-PP-MX-NA-GR-CT
defined solid angle α -particle counting with a PIPS detector	SA-PS-AP-00-00-00
4π (PPC)AX- γ (GeHP)-anticoincidence counting	4P-PP-MX-GH-GR-AC
4π CsI- β ,AX, γ counting	4P-CS-MX-00-00-HE
calibrated IC	4P-IC-GR-00-00-00
internal gas counting	4P-PC-BP-00-00-IG