AFRIMETS

Supplementary Comparison

on

Calibration of Pin Gauges

(AFRIMETS.L-S2.4.n01)

Renamed from (AFRIMETS.L-S5)

(2019-2022)

Final report

2024

Prepared by: Dr.Eng. Ahmed ElMelegy

Giza, Egypt

| Co | ntents | Page No. |
|-----|---|----------|
| | | |
| ABS | TRACT | 3 |
| 1. | INTRODUCTION | 4 |
| 2. | PARTICIPANTS | 5 |
| 3. | FORM OF COMPARISON | 5 |
| 4. | TIMETABLE | 6 |
| 5. | DESCRIPTION OF THE ARTIFACT: | 7 |
| 6. | CALIBRATION METHOD USED BY EACH PARTICIPANT | 8 |
| 7. | CALIBRATION RESULTS | 8 |
| 8. | TRACEABILITY | 9 |
| 9. | ANALYSIS OF THE RESULTS | 9 |
| 10. | CONCLUSION: | 15 |

<u>Abstract</u>

National Metrology Institutes from 8 African countries, namely Egypt, Nigeria, Kenya, Tanzania, Zambia, Zimbabwe, Botswana, and Mauritius have participated in an international supplementary comparison on the calibration of pin gauges. This comparison was a part of larger supplementary comparison between 13 African countries for the calibration of hand measuring instruments. This larger comparison which was carried out during the period between December 2019 – December 2022 has been piloted by NIS, Egypt and has been registered in BIPM-KCDB database on December 2019 with the identifier AFRIMETS.L-S5. The artifacts have been prepared by NIS, Egypt and measured before sent to circulate between all participant countries in round-robin scheme and returned back again for NIS, Egypt where a final measurement is made for stability check. The main purpose of these comparisons is to support submission of CMCs for calibration of hand length measuring instruments in BIPM-KCDB.

1. Introduction

In December 2019, the Egyptian National Institute of Standards (NIS), Egypt has initiated a comparison for the calibration of length hand measuring instruments which is considered the standard activity in most African metrology institutes. It was not possible to conduct comparison for the calibration all length hand measuring instruments, so a number of 6 hand measuring instruments have been selected, which are external micrometer, caliper, dial Gauge, setting rods, feeler gauges, and Pin gauges. The comparison was carried out during the period from December 2019 to December 2022 and was piloted by NIS, Egypt. The comparison has been registered in BIPM-KCDB database on December 2019 by the identifier AFRIMETS.L-S5 and was given the internal AFRIMET identifier AFRIMETS L11. The comparisons were carried out according to the protocol approved by all participants before initiating the comparison. The artifacts have been prepared and measured by NIS, Egypt before they were circulated between all participant countries in round-robin scheme and returned back again for NIS, Egypt where a final measurement was made for stability check. The main purpose of these comparisons is to support submission of CMCs for calibration of hand length measuring instruments in BIPM-KCDB.

In this report, 6 African countries, namely Egypt, Nigeria, Zambia, Zimbabwe, Botswana, and Mauritius have participated in an international supplementary comparison on the calibration of pin gauges. Five pin gauges which have nominal diameters of 0.5 mm, 0.75 mm, 1.0 mm, 5.05 mm and 10 mm are prepared by NIS, Egypt for the comparison.

2. <u>Participants</u>

6 African countries, namely Egypt, Nigeria, Zambia, Zimbabwe, Botswana, and Mauritius have participated in an international supplementary comparison on the calibration of pin gauges. NIS, Egypt was acting as the pilot laboratory. The rest of the 13 countries which are Morocco, Ghana, Ethiopia, Kenya, Tanzania, Malawi, and South Africa did not participate in the pin gauge comparison. The list of participants of this comparison are listed in the following table with their details:

| No. | Participant | Correspondence | E-mail Address Phone number | Address |
|-----|-----------------------------|---|---|---|
| | NIS (Pilot) | Osama Terra (Organizer) | <u>Osama.terra@gmail.com</u> +201141172900 | Tersa Street, Haram, Giza, Egypt. |
| 1 | (Egypt) | Ahmed Elmelegy (Pilot lab.) | <u>ahmedme3@yahoo.com</u> +201112145450 | P. code: 12211, P.O. Box: 136 Giza |
| 2 | NMI/SON (Nigeria) | Bede Obayi | <u>beobayi@yahoo.com</u> | 52, Lome Crescent, Zone 7, Wuse, Abuja |
| 2 | ZMA | Daniel Mutale | dmmutalezs@gmail.com | Zambia Metrology Agency Plot # 4526 Lechwe House |
| 5 | (Zambia) | | +260 955135366 | Freedom Way, Lusaka, Zambia. P.O.Box: 30989 Lusaka |
| 4 | SIRDC- NMI (Zimbabwe) | Burnhard Gandah | bgandah@sirdc.ac.zw burnhardg@gmail.com Tel: +263 778330014 | 1574 Alpes Road, Technology Drive Hatcliffe P.O. Box 6640 Harare |
| 5 | BOBS (Botswana) | Modiriemang Kame Pamidzani Ntima | kame@bobstandards.bw <u>Ntima@bobstandards.bw</u> <u>Pamidzani.ntima@gmail.com</u> Tel. (+267) 3903200 Tel. (+267) 72607660 | Private Bag B0 48 Gaborone |
| 6 | MSB (Mauritius) | Tomeswar Pryam Vaneeda Ramasawmy Pallut | <u>tpryam@msb.intnet.mu</u> <u>vramasawmy@msb.intnet.mu</u> +230 433 3648 | Mauritius Standards Bureau Villa Road, Moka Postal code – 80805 Mauritius |

Table 1 shows the participants NMIs in the pin gauge comparison

3. Form of Comparison

The comparison is made according to round robin scheme. All artifacts including the pin gauges are calibrated first at NIS, Egypt then shipped to the next country in the timetable, and so on<u>. Malawi withdrew from the comparison</u> since they were not ready by that time. Since not all countries participated in the 6 calibration activities,

participants will differ from one report to the others. For pin gauges, only 6 countries participated (shown in blue in figure 1).



Figure 1: The transportation sequence and measurements of the artifacts.

4. <u>Timetable</u>

The sequence of transferring the standards was made according to the protocol. However, delays occur due to the Covid-19 pandemic which took place at the start of the comparison in 2020. Table 2 shows the comparison planned timetable of the protocol. A delay of around one and half year almost from the planned time table.

| | Linu uait | Kemarks |
|-------------------|--|---|
| 25 November | 10 December | |
| 2019 | 2019 | |
| 11 December | 31 December | |
| 2019 | 2019 | |
| 1 January 2020 | 15 January 2020 | |
| 1 January 2020 | 15 January 2020 | |
| 16 January 2020 | 5 February 2020 | |
| 6 Eshmuany 2020 | 20 February | |
| o reditially 2020 | 2020 | |
| 21 February | 10 March 2020 | |
| 1 1 | 25 November 2019 11 December 2019 1 January 2020 6 January 2020 February 2020 21 February 2020 | 25 November 10 December 2019 2019 11 December 31 December 2019 2019 1 January 2020 15 January 2020 6 January 2020 5 February 2020 February 2020 20 February 2020 21 February 2020 10 March 2020 |

|--|

| Calibration at NMI/SON, Nigeria | 11 March 2020 | 25 March 2020 | |
|--|----------------------|----------------------|-----------|
| Delivery to NMIE, Ethiopia | 26 March 2020 | 15 April 2020 | |
| Calibration at NMIE, Ethiopia | 16 April 2020 | 30 April 2020 | |
| Delivery to KEBS, Kenya | 1 May 2020 | 20 May 2020 | |
| Calibration at KEBS, Kenya | 21 May 2020 | 5 June 2020 | |
| Delivery to TBS, Tanzania | 6 June 2020 | 26 June 2020 | |
| Calibration at TBS, Tanzania | 27 June 2020 | 12 July 2020 | |
| Delivery to MBS, Malawi | 13 July 2020 | 3 August 2020 | Withdrawn |
| Calibration at MBS, Malawi | 4 August 2020 | 20 August 2020 | |
| Delivery to ZABS, Zambia | 21 August 2020 | 10 September 2020 | |
| Calibration at ZABS, Zambia | 11 September 2020 | 30 September 2020 | |
| Delivery to SIRDC/NMI, Zimbabwe | 1 October 2020 | 20 October 2020 | |
| Calibration at SIRDC/NMI, Zimbabwe | 21 October 2020 | 5 November 2020 | |
| Delivery to BOBS, Botswana | 6 November 2020 | 26 November 2020 | |
| Calibration at BOBS, Botswana | 27 November 2020 | 12 December 2020 | |
| Delivery to MSB, Mauritius | 13 December 2020 | 2 January 2021 | |
| Calibration at MSB, Mauritius | 3 January 2021 | 18 January 2021 | |
| Delivery to NMISA, South Africa | 19 January 2021 | 9 February 2021 | |
| Calibration at NMISA, South Africa | 10 February 2021 | 28 February 2021 | |
| Delivery to NIS, Egypt | 1 March 2021 | 20 March 2021 | |
| Calibration at NIS, Egypt | 21 March 2021 | 5 April 2021 | |
| Final Chance for Submitting the Results | 6 April 2021 | 20 April 2021 | |
| Pre-Draft A | 21 April 2021 | 20 June 2021 | |

5. <u>Description of the artifact:</u>

NIS artifact is five pin gauges as shown in figure 2 that have nominal diameters of 0.5 mm, 0.75 mm, 1.0 mm, 5.05 mm and 10 mm.



Figure 2: photograph of pin gauges (similar one)

6. Calibration method used by each participant

Different methods are used by each participant for the calibration of pin gauges. The used methods by each participant are summarized in table 3

| _ | | | | | | | | |
|---|-----------------------|---|--|--|--|--|--|--|
| | Participant | Method used for calibration of pin gauges | | | | | | |
| 1 | NIS (Egypt) | 1 µm Comparator & Reference gauge blocks | | | | | | |
| 2 | NMI/SON (Nigeria) | NMI 0-1 inch digital Micrometer | | | | | | |
| 3 | ZMA (Zambia) | External Micrometer | | | | | | |
| 4 | SIRDC- NMI (Zimbabwe) | Gauge Blocks & Submicron micrometer | | | | | | |
| 5 | BOBS (Botswana) | Trimos | | | | | | |
| 6 | MSB (Mauritius) | Reference Micrometer & Gauge Block Set | | | | | | |

Table 3 methods used for calibration of pin gauges by each participant

7. Calibration results

The following table (table 4) shows the results for all participant in pin gauges calibration comparison. The results of each participant and the calibration uncertainty for the calibration of the five gauges are shown as a single row in table 4.

| r | | | r | Tuble 41 cul | ioration rea | Saits by caci | i participa | | | | |
|---|-----------------------------|---------|--------|--------------|--------------|---------------|-------------|---------|--------|---------|--------|
| | Instituto | Nominal | | Nominal | | Nominal | | Nominal | | Nominal | |
| | Country | 0.50 | U, mm | 0.75 | U, mm | 1.0 | U, mm | 5.05 | U, mm | 10.0 | U, mm |
| 1 | NIS (Egypt) (Pilot) | 0.499 | 0.0015 | 0.748 | 0.0015 | 0.999 | 0.0015 | 5.048 | 0.0015 | 9.999 | 0.0015 |
| 2 | NMI/SON (Nigeria) | 0.4980 | 0.0023 | 0.748 | 0.0026 | 0.998 | 0.0034 | 5.047 | 0.0148 | 9.998 | 0.0291 |
| 3 | ZMA (Zambia) | 0.500 | 0.003 | 0.750 | 0.003 | 1.000 | 0.003 | 5.050 | 0.003 | 10.004 | 0.003 |
| 4 | SIRDC- NMI (Zimbabwe) | 0.4990 | 0.0017 | 0.7489 | 0.0017 | 0.9989 | 0.0017 | 5.0486 | 0.0017 | 9.9989 | 0.0017 |
| 5 | BOBS (Botswana) | 0.499 | 0.0017 | 0.749 | 0.0020 | 0.999 | 0.0019 | 5.048 | 0.0015 | 10.000 | 0.0017 |
| 6 | MSB (Mauritius) | 0.500 | 0.004 | 0.748 | 0.004 | 0.999 | 0.004 | 5.048 | 0.004 | 9.999 | 0.004 |
| 1 | NIS (Egypt) (After) | 0.499 | 0.002 | 0.749 | 0.002 | 0.999 | 0.002 | 5.049 | 0.002 | 10.000 | 0.002 |

Table 4. Calibration results by each participant

8. <u>Traceability</u>

Reference for the calibration of the pin gauges should be traceable to SI unit of length though unbreakable traceability chain. The following table demonstrates the traceability of the measurement of each participant that are deduced from the calibration report.

Table 5. Traceability of calibration results by each participant.

| | Participant | Traceability |
|---|--------------------------|---|
| 1 | NIS (Egypt) | To SI units of length through NIS primary length standard (He Ne 633 laser) |
| 2 | NMI/SON (Nigeria) | Not mentioned |
| 3 | ZMA (Zambia) | To SI units of length through NMISA standards |
| 4 | SIRDC- NMI (Zimbabwe) | To SI units of length through NMISA standards |
| 5 | BOBS (Botswana) | To SI units of length through NMISA standards |
| 6 | MSB (Mauritius) | To SI units of length through gauge block set calibrated at NMISA |

The status of some NMIs having traceability through NMISA standards did not affect the analysis of comparison results.

9. Analysis of the results

9.1.<u>Transportation Stability</u>

Drifts of the artifact's values can occur during the transportation of the artifacts and handling over the long period of comparison. Therefore, a stability check must be performed to assure that this change will not affect the comparison results. The instability of the artifacts is assessed according to the following equation:

$$\Delta_{ins} = \left| x_{NIS_2} - x_{NIS_1} \right|$$

where, x_{NIS_2} is the measurement of the pilot (NIS, Egypt) after the comparison and x_{NIS_1} is the measurement of the pilot before the comparison. The instability of each artifact during the transportation will add additional contribution to the uncertainty of the reference value:

$$u_{ad}(x_i) = \frac{\Delta_{ins}}{2\sqrt{3}}$$

Additional criteria are applied to ensure the stability of the results which is:

$$\Delta_{ins} \leq 0.9 \sqrt{u_{CRV}^2 + u_{min}^2}$$

where, the u_{CRV} is the uncertainty in the comparison reference value and u_{min} is the uncertainty of the participant with the lowest uncertainty.

Therefore, the total combined uncertainty for each participant after adding the uncertainty due to the stability will be

$$u_a^2(x_i) = u^2(x_i) + u_{ad}^2(x_i)$$

| Nominal diameter, (mm) | Δ_{ins} (mm) | $u_{ad}(x_i)$ mm | $0.9\sqrt{u_{CRV}^2+u_{min}^2}$ mm | Status |
|------------------------|---------------------|------------------|------------------------------------|-----------|
| 0.50 | 0.0000 | 0.0000 | 0.00154 | Fulfilled |
| 0.75 | 0.0010 | 0.0003 | 0.00156 | Fulfilled |
| 1.00 | 0.0000 | 0.0000 | 0.00156 | Fulfilled |
| 5.05 | 0.0010 | 0.0003 | 0.00155 | Fulfilled |
| 10.00 | 0.0010 | 0.0003 | 0.00156 | Fulfilled |

Table 6. Stability measurement for each artifact

| Table 7. corre | ction of com | bined uncertaiı | nties for eac | h participant |
|----------------|--------------|-----------------|---------------|---------------|
|----------------|--------------|-----------------|---------------|---------------|

| | Institute, | Nominal | $u_a(x_i)$, | Nominal | $u_a(x_i),$ | Nominal | $u_a(x_i)$, | Nominal | $u_a(x_i)$, | Nominal | $u_a(x_i)$, |
|---|--------------------------|---------|--------------|---------|-------------|---------|--------------|---------|--------------|---------|--------------|
| | Country | 0.5 | mm | 0.75 | mm | 1.0 | mm | 5.05 | mm | 10.0 | mm |
| 1 | NIS (Egypt) (Pilot) | 0.499 | 0.0008 | 0.748 | 0.0009 | 0.999 | 0.0008 | 5.048 | 0.0009 | 9.999 | 0.0008 |
| 2 | NMI/SON (Nigeria) | 0.4980 | 0.0012 | 0.748 | 0.0014 | 0.998 | 0.0017 | 5.047 | 0.0074 | 9.998 | 0.0146 |
| 3 | ZMA (Zambia) | 0.500 | 0.0015 | 0.750 | 0.0016 | 1.000 | 0.0015 | 5.050 | 0.0016 | 10.004 | 0.0015 |
| 4 | SIRDC- NMI (Zimbabwe) | 0.4990 | 0.0009 | 0.7489 | 0.0010 | 0.9989 | 0.0009 | 5.0486 | 0.0010 | 9.9989 | 0.0009 |
| 5 | BOBS (Botswana) | 0.499 | 0.0009 | 0.749 | 0.0012 | 0.999 | 0.0010 | 5.048 | 0.0009 | 10.000 | 0.0009 |
| 6 | MSB (Mauritius) | 0.500 | 0.0020 | 0.748 | 0.0021 | 0.999 | 0.0020 | 5.048 | 0.0021 | 9.999 | 0.0020 |

9.2. <u>Reference value of the comparison</u>

The CRV (comparison reference value) was calculated using the weighted mean method according to the equation:

$$x_{CRV} = \sum_{i=1}^{N} w_i x_i$$

Where w_i is the weights and is calculated by the equation:

$$w_{i} = \frac{u_{a}^{-2}(x_{i})}{\sum_{i=1}^{N} u_{a}^{-2}(x_{i})}$$

and where u_a^2 is the uncertainty contribution of each participant including the uncertainty due to the stability analysis:

The standard uncertainty in the CRV value is calculated according to the following equation:

$$u(x_{CRV}) = \frac{\sqrt{\sum_{i=1}^{N} \frac{u^2(x_i)}{u_a^4(x_i)}}}{\sum_{i=1}^{N} u_a^{-2}(x_i)}$$

Calculation of the CRV and its uncertainty are given in table 8 and figure 3. The calculation is made after removing the inconsistent data according to section 9.3

| Nominal diameter, CRV value (diameter) (mm) (mm) | | Expanded Uncertainty (@ K=2), (mm) |
|--|---------|---------------------------------------|
| 0.50 | 0.49899 | 0.000817 |
| 0.75 | 0.74861 | 0.000864 |
| 1.00 | 0.99899 | 0.000868 |
| 5.00 | 5.04835 | 0.000848 |
| 10.00 | 9.99969 | 0.000874 |

Table 8. Comparison CRV and its uncertainty













Figure 3. The results of the participants in comparison with the CRV and it's uncertainty (expanded), a, b, c, d & e

9.3. Consistency check of the results

Before calculating the CRV and its uncertainty a consistency of the comparison results must be examined. To determine the consistency of comparisons results Chi-square value χ^2_{obs} is calculated according to the following equation:

$$\chi_{obs}^{2} = \sum_{i=1}^{n} \frac{(x_{i} - x_{CRV})^{2}}{u_{a}^{2}(x_{i})}$$
 3

For the data to be consistent, the following condition must satisfy

$$\Pr\{\chi^2(v) > \chi^2_{obs}\} < 0.05 \qquad 4$$

Where *v* is the degrees of freedom which is the number of participant and P_r denotes "probability of" and $\chi^2(v)$ is the inverse of the chi-square cumulative distribution function with degree of freedom specified by *v* for the probability of 0.05 (corresponding to the 95 % level of confidence). In this case, the participant with the highest value of χ^2_{obs} is excluded from the next round of evaluation and a new reference value, reference standard uncertainty, and chi-squared values are calculated again without the excluded laboratory. If the consistency check did not fail then y was accepted as the x_{CRV} and the $u(x_{CRV})$ are accepted. The number of participants N=6, therefore, the degrees of freedom $\upsilon = 5$. From the Chi-Square table at 95 % confidence level, we obtain $\chi^2_{0.05} = 11.07$.

| Nominal diameter, (mm) | χ^2_{obs} | $\chi^2_{0.05}$ (v=5) | Consistency $\chi^2_{obs} \le \chi^2_{0.05}$? |
|---------------------------|----------------|-----------------------|---|
| 0.50 | 1.450 | 11.07 | Satisfied |
| 0.75 | 1.627 | 11.07 | Satisfied |
| 1.00 | 0.804 | 11.07 | Satisfied |
| 5.00 | 1.448 | 11.07 | Satisfied |
| 10.00 | 9.722 | 11.07 | Satisfied |

| Table 9: Consistency | / check | (Not satisfied) |
|-----------------------------|---------|-----------------|
|-----------------------------|---------|-----------------|

9.4. Performance Evaluation

The purpose of the evaluation of performance methods is to provide a normalized performance evaluation so that all results are comparable and the performance of each participant can be measured. In such calibration schemes, the performance of the participants is evaluated by measuring whether the results of the participants are within the uncertainty of the CRV. The performance is evaluated using the normalized error number E_n , where;

$$E_n = \frac{(x_i - x_{CRV})}{\sqrt{U_{a_i}^2 + U_{CRV}^2}}$$

Where; x_i and U_{a_i} are the result and its corresponding adjusted expanded uncertainty of each participant, respectively. x_{CRV} and U_{CRV} are the CRV and its expanded uncertainty, respectively. E_n is interpreted as follows:

 $|E_n| \le 1 \rightarrow$ Satisfactory performance

 $|E_n| > 1 \rightarrow$ Unsatisfactory performance

| Nominal diameter, | | | | | | |
|-------------------|------|---------|------|-----------|------|------|
| (<i>mm</i>) | NIS | NMI/SON | ZMA | SIRDC-NMI | BOBS | MSB |
| 0.50 | 0.01 | 0.41 | 0.32 | 0.01 | 0.01 | 0.25 |
| 0.75 | 0.35 | 0.22 | 0.45 | 0.15 | 0.18 | 0.15 |
| 1.00 | 0.00 | 0.28 | 0.32 | 0.05 | 0.00 | 0.00 |
| 5.00 | 0.20 | 0.09 | 0.53 | 0.13 | 0.20 | 0.08 |
| 10.00 | 0.40 | 0.06 | 1.38 | 0.41 | 0.16 | 0.17 |

Table 10. Evaluation of performance for the participants using E_n

10.<u>Conclusion:</u>

• The results from 6 National Metrology Institutes from Egypt, Nigeria, Zambia, Zimbabwe, Botswana, and Mauritius have participated in an AFRIMET supplementary comparison on the calibration of pin gauges. The comparison reference value has obtained from the results using the weighted mean method after performing consistency check of the results using the Chi-square method. The Normalized error number En is used to evaluate the performance of all participants. All results are found satisfactory except Zambia (ZMA) at pin gauge of 10.0 mm diameter is found unsatisfactory (En>1).

List of References

[1] Guide to preparation of Key Comparison Reports in Dimensional Metrology (GD3), A Lewis, T Coveney 30 Nov 2020.

- [2] Measurement comparisons in the CIPM MRA, Guidelines for organizing, participating and reporting, CIPM MRA-G-11
- [3] M. G. Cox, "The evaluation of key comparison data", metrologia, 39, 589-595, 2002.